

# MARMOPOXY EXTRA-REMOVER / MARMOPOXY-REMOVER

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier: MARMOPOXY EXTRA-REMOVER / MARMOPOXY-REMOVER

Manufacturer / Importer / Supplier:

**ANAV INDUSTRIES**

Address: Khewat No. 1358/1151, Khatoni No.  
1461, Main NH-9, Near Toll Plaza, Village  
Rohad, Distt. Jhajjar, Haryana-124501

Marketed By:

**Marmo Solutions Pvt. Ltd.**

WHS 1/18, 2nd Floor, Kirti Nagar, New Delhi-15

**Tel. No: 011-40586081**

Emergency No: 91-9555155080

Web.: [www.marmosolutions.com](http://www.marmosolutions.com)

[info@marmosolutions.com](mailto:info@marmosolutions.com)



### MARMOPOXY EXTRA-REMOVER/MARMOPOXY-REMOVER

1. MarmoPoxy Extra-Remover/ MarmoPoxy-Remover is Eco-friendly cleaner, ready to use, for removing residues and streaks of epoxy resins, ideal for use in Greenbuilding. MarmoPoxy Extra-remover/MarmoPoxy-Remover has a specific cleaning action that removes residues and streaks from ceramic tile, porcelain tile and glass mosaic surfaces.

#### 1.1. Key Feature:

- (a) Water-based formulation
- (b) Non-toxic and non-hazardous
- (c) No environmental hazard rating

#### 1.2. Product Strength:

- (a) Highly effective
- (b) Floors and walls
- (c) Suitable for use with compact and porous materials

Product Name: **MARMOPOXY EXTRA-REMOVER/MARMOPOXY-REMOVER**

# MARMOPOXY EXTRA-REMOVER / MARMOPOXY-REMOVER

## 2. Usage Area:

### 2.1. Use:

-To eliminate residues and streaks of Epoxy/Epoxy grout from ceramic surfaces.

### 2.2 Substrates:

-ceramic and homogeneous tiles  
-glass mosaic

### 2.3. Do not use:

-On surfaces that are not resistant to basic agents.  
-On marble and natural stone it is advisable to carry out a test in advance

## 3. Usage Instruction:

**3.1. Preparation:** The coating material must be firstly cleared to remove any dust. Epoxy/ Epoxy grout must be fully hardened.

**3.2. Preparation:** Marmopoxy Extra Remover is a ready-to-use transparent liquid. Shake the bottle well before opening in order to re-disperse the liquid evenly.

### 3.3. Application:

- (a) It is advisable to perform a preliminary test on tiles that are not to be laid, or in a concealed area.
- (b) Apply MarmoPoxy Extra Remover evenly to the surface to be cleaned with a white rough scrubbing pad and leave it until the dirt to be removed begins to visibly lift; this may take a few minutes or up to 3 – 5 minutes depending on the quantity, the elapsed time after laying (at least 7 days) and the degree of absorption of the surface.
- (c) Scrape the surface mechanically with abrasive felt pads.
- (d) Once cleaned, rinse well and dry carefully.
- (e) The use of wet vacuum makes the operation easier and ensures the complete removal of residue.
- (f) In the case of large surface areas, a mechanical buffer with an abrasive felt pad for the removing operation is recommended.
- (g) Repeat for highly stubborn dirt.

**3.4. Cleaning:** Residues of Marmopoxy extra-remover can be cleaned from tools by rinsing them thoroughly with water.

Product Name: **MARMOPOXY EXTRA-REMOVER/MARMOPOXY-REMOVER**

## MARMOPOXY EXTRA-REMOVER / MARMOPOXY-REMOVER

**4. Abstracts:** Remove residues and streaks of Epoxy/ Epoxy grout from ceramic tiles, porcelain tiles, glass mosaic, with an eco-friendly, water-based detergent, Eco 3 GreenBuilding Rating®, such as Marmopoxy extra-remover by Marmo India. Apply evenly to the surface to be treated, remove dirt with mechanical means, rinse thoroughly and dry carefully, for an average coverage of 1 ℓ = 10 – 20 m<sup>2</sup>.

### TECHNICAL DATA COMPLIANT WITH MARMO QUALITY STANDARD

<b>Appearance</b>	<b>Milky White</b>
<b>Specific Weight</b>	<b>=1,05 kg/dm<sup>3</sup></b>
<b>Shelf Life</b>	<b>= 24 months in the original packaging</b>
<b>Warning</b>	Protect from frost, avoid direct exposure to sunlight and sources of heat
<b>Pack</b>	<b>Bottles 1 L</b>
<b>Water Dilution ratios</b>	<b>All ratios</b>
<b>Viscosity</b>	<b>=1540 mPa.s, rotor 2 RPM 50</b>
<b>pH</b>	<b>=1,4</b>
<b>Temperature range for application</b>	<b>From +5°C to +35°C</b>
<b>Waiting time before cleaning with water</b>	<b>= 2-5 min.</b>
<b>Coverage</b>	<b>=10-20m<sup>2</sup>/1 L</b>

### 3. Warning:

- (a) Product for professional use
  - (b) abide by any standards and national regulations
  - (c) store and use at a temperature above +5 °C. Protect from frost
  - (d) Rinse thoroughly all surfaces treated
  - (e) Do not leave cans or bottles open, even during use
  - (f) wear protective gloves and goggles
  - (g) leaving the product to act for more than 5 minutes may result in physical and colour alterations in the grout
  - (h) if necessary, ask for the safety data sheet
- for any other issues, contact the Marmo Solutions Pvt Ltd, 01140586081, [info@marmosolutions.com](mailto:info@marmosolutions.com)

Product Name: **MARMOPOXY EXTRA-REMOVER/MARMOPOXY-REMOVER**