

MARMOSHINE-LLQUID PLUS

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier: MARMOSHINE-LIQUID PLUS

Manufacturer / Importer / Supplier:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151, Khatoni No.
1461, Main NH-9, Near Toll Plaza, Village
Rohad, Distt. Jhajjar, Haryana-124501

Marketed By:

Marmo Solutions Pvt. Ltd.

WHS 1/18, 2nd Floor, Kirti Nagar, New Delhi-15

Tel. No: 011-40586081

Emergency No: 91-9555155080

Web.: www.marmosolutions.com

info@marmosolutions.com



MARMOSHINE-L PLUS

1. MarmoShine L Plus has been developed as a simple-to-use restoration system for marble, terrazzo and polished limestone floors. Marmo Shine L Plus produces a very high polish. The newly restored surface will resist scuffs and scratches. This restored surface will be very durable. Marmo Shine L Plus dries as you buff and therefore requires no messy clean-up.

2. Direction:

2.1. **CAUTION:** Since marble and limestone is a product of nature and their components can vary, they may react differently to this product. For this reason, always test in a small inconspicuous area for adverse reactions.

2.2. SURFACE PREPARATION:

(a) Surface must be clean and dry.

Product Name: **MARMOSHINE-LIQUID PLUS**

MARMOSHINE-LLQUID PLUS

- (b) On floor surfaces, make sure all waxes, floor finish or other coatings are removed.
- (c) If there is a coating on the floor, use Marmo Cleaner Mild for removal.
- (d) Rinse surface thoroughly with water and air dry prior to crystallization.

2.3. PLEASE NOTE: Worn out or damaged surfaces may require resurfacing prior to crystallization. Make sure to cover any sensitive surfaces such as metals, glass, carpet, etc. that may be exposed to over-spray.

2.4. APPLICATION:

- (a) Use a 175 RPM Floor machine designed for crystallization (130 - 180 lbs.), equipped with a #0 or #1 grade steel wool pad.
- (b) Apply Marmo Shine L Plus (with a spray bottle with trigger) at a rate of 2 to 3 squirts per square yard (.836 sq. meter) and immediately buff until surface is completely dry.
- (c) Buff in both directions until desired gloss is achieved.
- (d) Marmo Shine L Plus yields approximately 2000-5000 square feet (185 - 465 sq. meters) per gallon of coverage.
- (e) For daily maintenance after re-polishing, use the SCS Daily Maintenance System marmot manual for more information. **NOTE: Shake lightly before use.**

3. Specification:

Product Type	Vitrification compound
Appearance	Opaque Liquid
Odor	Mild, bland
Specific Gravity (g/cc)	1.08 ± 0.01
pH (concentrate)	2.3 ± 0.2
Flash Point	None
Safe on stone	Yes
Scuff Resistance	Excellent
Scratch Resistance	Excellent
Increased Gloss	Outstanding
UL Classified	Yes

Product Name: **MARMOSHINE-LIQUID PLUS**

MARMOSHINE-LLQUID PLUS

1. Safety Information:

1.1. **DANGER:** HARMFUL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE. CAUSES SKIN IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF REACH OF CHILDREN.

1.2. Precautionary Statements:

1.2.1. Prevention:

- (a) Use only outdoors or in a well-ventilated area.
- (b) Do not breathe mist or vapour.
- (c) Wear protective gloves/protective clothing/eye protection/face protection.
- (d) Do not eat, drink or smoke when using this product.
- (e) Wash hands thoroughly after handling.

1.2.2. Response:

- (a) **If swallowed:** Rinse mouth. Do NOT induce vomiting.
- (b) **If on skin (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
- (c) **If inhaled:** Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/ doctor.
- (d) **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

1.2.3. **Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container in accordance with local/ regional/national/ international regulations. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. For Commercial and Industrial Use Only

Product Name: **MARMOSHINE-LIQUID PLUS**