# MARMOSHINE-WAX BASE

MARMO SOLUTIONS Marble & Tile Solution Products

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

**1.1 Product identifier: MARMOSHINE-W** 

Manufacturer / Importer / Supplier: **ANAV INDUSTRIES** Address: Khewat No. 1358/1151, Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village Rohad, Distt. Jhajjar, Haryana-124501

Marketed By: Marmo Solutions Pvt. Ltd. WHS 1/18, 2nd Floor, Kirti Nagar, New Delhi-15

Tel. No: 011-40586081 Emergency No: 91-9555155080 Web.: www.marmosolutions.com info@marmosolutions.com



1.Marmo Solutions "Marmoshine Wax Base" is a solvent-containing product made of highly efficient waxes and synthetic resins. Treated areas obtain a brilliant, anti-slippery surfaces and the colour is well intensified.

### 2. Application field:

(a) Marmo Solution "Marmoshine Wax Base" is suited for the care of floors, staircases or window sills out of fine-ground or polished natural and cast stones, s.a. marble, granite, slate, terrazzo, travertine and similar for indoor use.

(b) It is especially suited to fresh up the colour and gloss of dull and worn stone floors. **3.Usage Process:** 

a)Clean the surfaces thoroughly with marmo solution "Cleaner mild". They must be clean and absolutely dry before use of Marmoshine Wax Base. Ideal temperature for application 15 - 25°C.

Product Name: MARMOSHINE-WAX BASE



Marketed By: Marmo Solutions Pvt. Ltd. WHS 1/18, 2nd Floor, Kirti Nagar, New Delhi-15 Customer No.: 011-40586081 Web.: www.marmosolutions.com

#### **TECHNICAL DATA SHEET**

# MARMOSHINE-WAX BASE



b)Repeat application on very absorbent, non polished surfaces.

c)Polish surfaces with a soft cloth or a white nylon pad and a floor polishing machine when their appearance has become dull.

d)For regular cleaning use Marmo Solutions "Cleaner mild"

#### 4.Notes:

(a)Storage at a temperature of 25 - 30° C will render it ready to be worked again.
(b)Films of Marmoshine Wax Base can be removed by marmo solutions "Poxy remover".
(c)Objects in the working area which are not resistant to solvents, s.a. various synthetic materials, rubber, lacquered areas, must be protected.

(d)At temperatures below 13°C the product becomes viscous below 9° it will become almost solid.

(e)For adequate waste disposal container must be completely emptied.

(f)Apply the product in a thin layer, only, otherwise the surfaces will not take a good polish.

## 5. Safety measures: see EC safety data sheet

| 6. Technical Data: |   |
|--------------------|---|
| Coverage           | approx. 15 – 30 m <sup>2</sup> / litre              |
| Colour             | Slightly yellowish /Clear                           |
| Density            | Approx. 0.87 g/cm <sup>3</sup>                      |
| Shelf life         | 3 years approx. If stored in cool place free        |
|                    | from frost in its tightly closed original container |

**7. Notice:** the above information is based on the latest stage of technical progress. It is to be considered as a non-binding hint and does not release the user from a performance test, since application, processing and environmental influences are beyond our realm of control.

Product Name: MARMOSHINE-WAX BASE



Manufactures By: **Anav Industries** Khewat No. 1358/1151, Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village Rohad, Distt. Jhajjar, Haryana-124501 | Mob.: +91-7982940118

Marketed By: Marmo Solutions Pvt. Ltd. WHS 1/18, 2nd Floor, Kirti Nagar, New Delhi-15 Customer No.: 011-40586081 Web.: www.marmosolutions.com

For any query/feedback E-mail: info@marmosolutions.com