

TECHNICAL DATA SHEET

Product Name:MARMOPOXY-REMOVER

Manufacturer :

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MARMO SOLUTIONS PVT. LTD.

Office Address :

MUMBAI:47A, Ground And First Floor, Parmar Compound, Highway Road, Vile Parle East, Mumbai - 400099

DELHI:WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi - 110 015

Tel. No: +91 11 40586081

Website: www.marmosolutions.com

E-Mail ID: info@marmosolutions.com

Office hours: Monday to Saturday (10AM-6PM)

1. Product Description:

Marmopoxy-Remover is a specially formulated liquid solution designed to effectively dissolve and remove uncured epoxy, adhesives, and resins from natural stone, tiles, and other surfaces. It penetrates deeply to break down resinous materials, allowing for easy removal without damaging the substrate.



TECHNICAL DATA SHEET

Product Name: MARMOPOXY-REMOVER

Product Features:

- **Effective Epoxy Removal:** Dissolves uncured epoxy, adhesives, and resins quickly and efficiently.
- **Surface-Safe:** Designed to be safe on natural stones like marble and granite without causing damage.
- **Non-Acidic Formula:** Free from acidic components, preventing surface etching or corrosion.
- **User-Friendly:** Easy to apply with minimal labor required.
- **Low Odor:** Low VOC content ensures minimal odor during application.

Applications:

- Removal of uncured epoxy from natural stones like marble, granite, and limestone.
- Cleaning epoxy residues from tiles and other construction surfaces.
- Safe for use on most substrates including porcelain, ceramic, and concrete.

Application Guidelines :

- **Preparation:** Ensure the surface is dry and free from any loose debris.
- **Application:** Pour a sufficient amount of Marmopoxy-Remover directly onto the area with uncured epoxy or residue.



TECHNICAL DATA SHEET

Product Name: MARMOPOXY-REMOVER

- **Dwell Time:** Allow the product to sit on the surface for 10-20 minutes to break down the epoxy.
- **Removal:** Use a soft scrub brush or a microfiber cloth to gently agitate and remove the softened epoxy.
- **Rinse:** Clean the surface with warm water and a soft microfiber towel to remove any remaining residue.

Technical Specifications:

- **Appearance:** Transparent or slightly yellow liquid
- **Density:** 0.9 - 1.1 g/cm³
- **Viscosity:** Low viscosity
- **pH Level:** Neutral
- **Flash Point:** >70°C
- **Odor:** Mild, solvent-like
- **Solubility in Water:** Insoluble
- **Shelf Life:** 12 months in original, unopened packaging
- **Application Temperature:** 5°C - 35°C (Ambient and Surface Temperature)
- **Coverage:** 5 - 10 m² per liter, depending on surface porosity
- **Dwell Time:** 10 - 20 minutes (may vary based on thickness)
- **Cleaning Method:** Use water and microfiber cloth after application



TECHNICAL DATA SHEET

Product Name: MARMOPOXY-REMOVER

Storage & Handling:

- **Storage:** Store in a cool, dry place (5°C - 30°C), away from direct sunlight and heat. Keep the container tightly sealed.
- **Handling:** Use in a ventilated area. Wear gloves and eye protection. Avoid skin and eye contact.

Health & Safety:

- **Protective Gear:** Always wear gloves, eye protection, and protective clothing during use to avoid skin and eye contact.
- **Ventilation:** Use in a well-ventilated area to avoid inhalation of vapors.
- **Skin Contact:** Wash immediately with soap and water.
- **Eye Contact:** Rinse thoroughly with water and seek medical advice if irritation persists.
- **Inhalation:** Move to fresh air if feeling unwell; seek medical help if symptoms continue.
- **Ingestion:** Do not induce vomiting. Seek medical attention immediately.
- **Disposal:** Follow local regulations for the safe disposal of chemical products.

