

TECHNICAL DATA SHEET

Product Name: MARMOMASTIC THASSOS LIQUID

Registered Office:

MARMO SOLUTIONS PVT. LTD.

(AN ISO 9001:2015 CERTIFIED COMPANY)

MUMBAI: 47A, Ground And First Floor, Parmar

Compound, Highway Road, Vile Parle East,

Mumbai – 400099

DELHI : WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi - 110015

Customer No: +91 11 40586081

Web.: www.marmosolutions.com

For any query/feedback

E-Mail: info@marmosolutions.com

CIN : U74140DL2013PTC252178

E-Mail ID: info@marmosolutions.com

Office hours: Monday to Saturday (10AM-6PM)



1. Product Description:

MARMOMASTIC-THASSOS LIQUID is a premium two-component liquid polyester mastic specially formulated for filling joints, pinholes, hairline cracks, and surface imperfections in white and light-coloured natural stones. Its low-viscosity, self-levelling formulation ensures excellent penetration into fine gaps, providing seamless repairs with outstanding adhesion and colour stability.

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai- 400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com

TECHNICAL DATA SHEET

Product Name: MARMOMASTIC THASSOS LIQUID

2. Product Features:

- Premium liquid polyester mastic.
- Low-viscosity, self-levelling formulation.
- Crystal-clear, non-yellowing finish.
- Specially developed for white and translucent stones.
- Excellent penetration into fine joints and pinholes.
- Rapid curing for faster fabrication.
- High bond strength and excellent adhesion.
- Smooth surface finish for easy sanding and polishing.
- Excellent colour stability after curing.

3. Application:

- Filling joints and gaps
- Filling pinholes and surface pores
- Hairline crack repairs
- Surface levelling
- Seamless stone repairs
- Horizontal stone applications
- Stone fabrication and finishing
- Countertop joint filling

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai- 400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com

TECHNICAL DATA SHEET

Product Name: MARMOMASTIC THASSOS LIQUID

4. Product Specifications:

- **Base:** Unsaturated Polyester Resin
- **Appearance:** Clear Liquid
- **Consistency:** Low Viscosity Liquid
- **Packaging:** 1 kg (Resin) + 30 gm (Hardener)
- **Bond Strength:** $>2.5 \text{ N/mm}^2$
- **Pot Life (25°C):** 15-20 Minutes
- **Tack-Free Time :** 25-40 minutes
- **Polishable:** Yes
- **Full Curing Time:** 8-12 hours
- **Bond Strength:** $> 2.5 \text{ N/mm}^2$
- **Compressive Strength:** $>60 \text{ N/mm}^2$
- **Density:** $1.02 \pm 0.05 \text{ g/cm}^3$
- **Application Temperature:** 15°C to 35°C
- **Shelf Life:** 12 months in original, unopened packaging

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai- 400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com

TECHNICAL DATA SHEET

Product Name: MARMOMASTIC THASSOS LIQUID

5. Application Guidelines:

Surface Preparation: Ensure all bonding surfaces are clean, dry, and free from dust, oil, grease, wax, and loose particles.

Mixing: Mix 1kg MARMOMASTIC-THASSOS LIQUID with 30 gm parts hardener (by weight) until a homogeneous mixture is achieved.

Application

Pour or spread the mixed mastic over the joints or repair area using a spatula or flexible scraper. Allow the material to flow naturally into gaps and surface imperfections. Then, remove excess material before curing.

Curing

Allow the adhesive to cure completely before sanding, machining, grinding, or polishing. Typical curing time: 8–12 hours at 25°C.

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai- 400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com

TECHNICAL DATA SHEET

Product Name: MARMOMASTIC THASSOS LIQUID

6.DO'S & DON'TS

• DO'S

- Do ensure the stone surface is clean, dry, and free from dust, grease, and loose particles before application.
- Do mix the resin and hardener thoroughly in the recommended ratio.
- Do use clean tools and mixing containers to prevent contamination.
- Do allow the liquid mastic to penetrate naturally into joints and fine gaps.
- Do remove excess material before it hardens.
- Do perform a compatibility test on a small area before large-scale application.
- Do sand and polish the repaired area only after complete curing.
- Do store the product in its original tightly sealed container in a cool, dry place.

• DON'TS

- Do not alter the recommended resin-to-hardener ratio.
- Do not apply on wet or damp surfaces.
- Do not use the mixed product beyond its working time.
- Do not dilute with solvents or mix with other adhesives.
- Do not use for large vertical gaps or overhead repairs; use MARMOMASTIC-THASSOS GEL for non-sag applications.
- Do not expose uncured repairs to water or heavy mechanical loads.
- Do not machine or polish before complete curing.
- Do not return mixed material to the original container.

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai-400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com

TECHNICAL DATA SHEET

Product Name MARMOMASTIC THASSOS LIQUID

7.Storage and Handling:

- **Storage:** Store in a cool, dry place (5°C - 30°C), away from direct sunlight and heat. Keep the container tightly sealed.
- **Handling:** Use in a ventilated area. Wear gloves and eye protection.
Avoid skin and eye contact.

Health & Safety:

- **Protective Gear:** Always wear gloves, eye protection, and protective clothing during use to avoid skin and eye contact.
- **Ventilation:** Use in a well-ventilated area to avoid inhalation of vapors.
- **Skin Contact:** Wash immediately with soap and water.
- **Eye Contact:** Rinse thoroughly with water and seek medical advice if irritation persists.
- **Inhalation:** Move to fresh air if feeling unwell, seek medical help if symptoms continue.
- **Ingestion:** Do not induce vomiting. Seek medical attention immediately.
- **Disposal:** Follow local regulations for the safe disposal of chemical products.

Manufactured by:

ANAV INDUSTRIES

Address: Khewat No. 1358/1151,

Khatoni No. 1461, Main NH-9, Near Toll Plaza, Village

Rohad, Dis. Jhajjar, Haryana-124501

Marketed By/ Exporter:

MUMBAI: 47A, Ground And First Floor,

Parmar Compound, Highway Road,

Vile Parle East, Mumbai- 400099

DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near

Richi Rich, New Delhi- 110 015

Tel. No: +91 11 40586081



www.marmosolutions.com



For any query/feedback

E-Mail: info@marmosolutions.com