MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS



TECHNICAL DATA SHEET

Product Name: MARMOLATEX-ECO

Registered Office:

MARMO SOLUTIONS PVT. LTD.

(AN ISO 9001:2015 CERTIFIED COMPANY)

MUMBAI: 47A, Ground And First Floor, Parmar Compound, Highway Road, Vile Parle East, Mumbai – 400099

DELHI : WHS, 1/18, 2nd Floor Kirti Nagar, Near Richi Rich, New Delhi - 110015

Customer No: +91 11 40586081

Web.: www.marmosolutions.com

For any query/feedback

E-Mail: info@marmosolutions.com

CIN : U74140DL2013PTC252178

E-Mail ID: info@marmosolutions.com

Office hours: Monday to Saturday (10AM-6PM)

1. Product Description:

Marmolatex-Eco is a premium admixture latex resin designed to significantly enhance the performance of C1 or C2 type cementitious adhesives. Its formulation improves flexibility, adhesion, and overall mechanical strength, making it suitable for demanding applications. When combined with CITE Marmoflex, it enables deformability to achieve S1 classification, providing enhanced performance for tiling systems under high-stress conditions.

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

TECHNICAL DATA SHEET

Product Name: MARMOLATEX-ECO

2. Product Features:

- **Increased Flexibility:** Enhances the deformability of adhesives, allowing movement and stress absorption.
- **Superior Adhesion:** Improves bond strength between adhesive and substrate.
- **Enhanced Strength:** Boosts mechanical properties, providing longer- lasting and durable installations.
- **Versatile Performance:** When mixed with Marmoflex, it can be tailored to specific needs, achieving both C2TES1 performance levels.

3. Performance Classification:

- **Mixing Ratio:** 100% Marmolatex-Eco C2TES1 (High-performance adhesive with extended open time and high deformability)
- **Property Value:** Appearance Milky white liquid
- **Density:** ~1 .05 g/cm³
- **pH:** 7-9
- **Solid Content:** ~ 15%
- **Deformability:** Class S1 (with 100% Marmolatex-Eco)
- **Application Temperature:** +5°C to +35°C
- **Open Time:** Extended (as per C2 classification)
- **Pot Life:** 4-6 hours (depending on temperature)
- **Shelf Life:** 6 months in original unopened packaging
- **Packaging:** 5L containers

Marketed By/ Exporter:
MUMBAI: 47A, Ground And First Floor,
Parmar Compound, Highway Road,
Vile Parle East, Mumbai- 400099
DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near
Richi Rich, New Delhi- 110 015
Tel. No: +91 11 40586081

MADE IN INDIA

For any query/feedback
E-Mail: info@marmosolutions.com

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

TECHNICAL DATA SHEET

Product Name: MARMOLATEX-ECO

4. Application Guidelines:

1. **Surface Preparation:** Ensure substrates are clean, dry, and free from dust, grease, or any contaminants.

2. **Mixing Instructions:** C2TES1 Performance Mix 100% Marmolatex-Eco with CITE Marmoflex adhesive.

3. Application Method:

• Use a suitable notched trowel to apply the mixed adhesive.

• Follow the standard application procedures for ceramic tiles and stones.

• Ensure the adhesive achieves full contact with the tile back and substrate.

4. Curing:

• Ensure adequate curing time before permitting heavy foot traffic or starting the grouting process.

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

Marketed By/ Exporter:
MUMBAI: 47A, Ground And First Floor,
Parmar Compound, Highway Road,
Vile Parle East, Mumbai- 400099
DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near
Richi Rich, New Delhi- 110 015
Tel. No: +91 11 40586081

www.marmosolutions.com

MADE IN INDIA
For any query/feedback
E-Mail: info@marmosolutions.com

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

TECHNICAL DATA SHEET

Product Name: MARMOLATEX-ECO

5.DO'S & DON'TS

- **DO'S**
- Ensure the substrate is clean, sound, and free from dust, oil, grease, and loose particles before application.
- Apply the mixed adhesive using a suitable notched trowel for uniform coverage.
- Ensure full contact between tile back and substrate for proper bonding.
- Allow adequate curing time before permitting foot traffic or starting grouting.

- **DON'TS**
- Do not apply on dirty, dusty, or contaminated surfaces.
- Do not mix the product with any other additives or chemicals.
- Do not apply adhesive beyond its open time after mixing.
- Do not expose freshly installed tiles to heavy traffic before curing.
- Do not store the product in direct sunlight or extreme heat.

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

Marketed By/ Exporter:
MUMBAI: 47A, Ground And First Floor,
Parmar Compound, Highway Road,
Vile Parle East, Mumbai- 400099
DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near
Richi Rich, New Delhi- 110 015
Tel. No: +91 11 40586081

www.marmosolutions.com

MADE IN INDIA
For any query/feedback
E-Mail: info@marmosolutions.com

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

TECHNICAL DATA SHEET

Product Name: MARMOLATEX-ECO

6.Storage and Handling:

• Storage:

Store in a cool, dry place away from moisture. Keep the packaging sealed when not in use.

• Handling:

Wear protective gloves and goggles while handling the product.
In case of skin or eye contact, rinse thoroughly with clean water. If inhaled, move to fresh air and seek medical attention if necessary.

• Health and Safety:

Refer to the product's Safety Data Sheet (SDS) for detailed information on safe handling practices, disposal, and health precautions. Follow local regulations regarding product handling and disposal.

MARMO SOLUTIONS
MARBLE & TILE SOLUTION PRODUCTS

Marketed By/ Exporter:
MUMBAI: 47A, Ground And First Floor,
Parmar Compound, Highway Road,
Vile Parle East, Mumbai- 400099
DELHI: WHS, 1/18, 2nd Floor Kirti Nagar, Near
Richi Rich, New Delhi- 110 015
Tel. No: +91 11 40586081

www.marmosolutions.com

MADE IN INDIA
For any query/feedback
E-Mail: info@marmosolutions.com